

Technical Parameters

Type	Primary amps turns	Outline dimensions					Moulding Dimensions				Corresponding accuracy class
		H	h	C	L	B	a	e	L1	L2	
BH1-0.66 30 Core	50~250	80			60	36	31	11	32	59	10.5 0.2 0.5S 0.2S
BH1-0.66 40 Core	200~600	98	89		75	40	42	11	44	59	10.5 0.2 0.5S 0.2S
BH1-0.66 50 Core	400~1000	98	92		82	40	52	16	50	59	10.5 0.2 0.5S 0.2S
BH1-0.66 60 Core	600~1500	126	100		102	40	60	21.5	50	59	10.5 0.2 0.5S 0.2S
BH1-0.66 80 Core	600~2000	118	100		125	40	82	20	50	59	10.5 0.2 0.5S 0.2S
BH1-0.66 100 Core	800~1500	136.5	105		170	40	105	30	50.5	59	10.5 0.2 0.5S 0.2S
BH1-0.66 120 Core	1500~3000	138	125		190	46	125	36	50	59	10.5 0.2 0.5S 0.2S
BH2-0.66 30 Core	50~300	98	125		75	40	31	11	44	59	10.5 0.2 0.5S 0.2S
BH2-0.66 40 Core	200~600	104	149		78.5	46	42	31	44	59	10.5 0.2 0.5S 0.2S
BH2-0.66 50 Core	400~1000	106	175		87	46	52	31.5	54	59	10.5 0.2 0.5S 0.2S
BH2-0.66 60 Core	600~1500	111	200		102	48	62	31.5	54	59	10.5 0.2 0.5S 0.2S
BH2-0.66 80 Core	600~2000	107.5	125		122	46	83	32.5	60.5	59	10.5 0.2 0.5S 0.2S
BH2-0.66 100 Core	800~2000	122	149		140	50	102	32	74.5	59	10.5 0.2 0.5S 0.2S
BH2-0.66 120 Core	1500~3000	153	175		169	48	122	52	54.5	59	10.5 0.2 0.5S 0.2S
BH3-0.66 60 Core	600~2000	147	200		105	43	62	52	48	59	10.5 0.2 0.5S 0.2S
BH3-0.66 80 Core	600~2000	148	131		122.5	45	82	52	60	59	10.5 0.2 0.5S 0.2S
BH3-0.66 100 Core	800~2000	154	132		148	44	102	52	78	59	10.5 0.2 0.5S 0.2S
BH3-0.66 150 Core	2000~5000	161	138		202	48	156	53	80	59	10.5 0.2 0.5S 0.2S
BH4-0.66 30 Core	50~250	78.5	145		60.5	36	31	11	32	59	10.5 0.2 0.5S 0.2S
BH4-0.66 40 Core	200~600	101	64		79	46	42	11	47	59	10.5 0.2 0.5S 0.2S
BH4-0.66 50 Core	400~1000	104	82		88	46	52	11	44	59	10.5 0.2 0.5S 0.2S
BH4-0.66 60 Core	600~1500	112	82		125	56	62	33		67	10.5 0.2 0.5S 0.2S
BH4-0.66 80 Core	600~2000	112	110		149	56	83	33	48	67	10.5 0.2 0.5S 0.2S
BH4-0.66 100 Core	800~2000	117	102		175	56	103	33	58	67	10.5 0.2 0.5S 0.2S
BH4-0.66 120 Core	1500~3000	137	120.5		200	56	122	52	75	67	10.5 0.2 0.5S 0.2S
BH5-0.66 60 Core	600~2000	137	122		100	56	33	62		67	10.5 0.2 0.5S 0.2S
BH5-0.66 80 Core	600~2000	161	82		100	56	33	83	48	67	10.5 0.2 0.5S 0.2S
BH5-0.66 100 Core	800~2000	187	88		105	56	33	103	58	67	10.5 0.2 0.5S 0.2S
BH5-0.66 120 Core	1500~3000	212	90		125	56	52	122	75	67	10.5 0.2 0.5S 0.2S
BH6-0.66 60 Core	600~2000	137	95	100	112	56	33	62		67	10.5 0.2 0.5S 0.2S
BH6-0.66 80 Core	600~2000	161	95.1	100	112	56	33	83	48	67	10.5 0.2 0.5S 0.2S
BH6-0.66 100 Core	800~2000	187	106	105	117	56	33	103	58	67	10.5 0.2 0.5S 0.2S
BH6-0.66 120 Core	1500~3000	212	137	125	137	56	52	122	75	67	10.5 0.2 0.5S 0.2S